

FLOOR CARE MAINTENANCE

Once your floor is coated with Intergrain Enviropro coatings, it is important that the below measures are taken to prolong the life of your floor and maintain a high performance finish.

Use of Floor after Coating

- Light foot traffic may be possible after 24 hours in drying conditions of 25 °C and 50% relative humidity.
- It is advised that no shoes are worn on the timber floor for the first 72 hours after drying.
- Avoid dragging furniture over coated surface.

Protect the floor's surface with mats, rugs and protective pads

- Place mats at entrances and where possible place a mat on the inside as well as outside.
- Use rugs in high traffic areas.
- It is recommended that mats be placed on the timber floor 14 days after the coating is applied.
- Ensure protective pads are on all furnishing floor contact points.



Filter Light with Curtains and Blinds

- To avoid fading and discolouring of your timber floor, filter direct light with curtains and blinds.

Cleaning Your Timber Floor

- Use an **anti-static dust mop** regularly to collect dust and dirt.
- It is advised not to use vacuum cleaners because often the brushes on the vacuum head wear thin and the metal scratches the floor.
- Wash your timber floor weekly (or more if required) with a damp mop using **Intergrain Enviropro Squeaky Clean**. Do not flood the floor.

RECOMMENDED MAINTENANCE PRODUCTS

Wash your timber floors with **Intergrain Enviropro Squeaky Clean**

- **Squeaky Clean** is a multi purpose, environmentally responsible cleaner that will help prolong the life of floors and improve the appearance throughout the life of the floor.
- **Squeaky Clean** is suitable for use on timber and parquet floors, as well as hard surfaces such as vinyl, tiles and sealed concrete.
- **Squeaky Clean** can also be used neat (without water) to assist in the removal of black heel marks or stubborn stains.



Rejuvenate your timber floors with **Intergrain Enviropro Renew**

- **Renew** is a high performance, water based polish for restoring of the surface finish on all coated floors.
- Use **Renew** when there are obvious visible signs of wear on the floor.

