



TECHNICAL BULLETIN

Endure 1 Pack and 2 Pack with added Intergrain UltraGrip

Intergrain UltraGrip is a slip resistant additive that can be used with Endure 1 Pack Satin and 2 Pack Satin, to give a coating that is slip resistant.

When UltraGrip is added to these two Endure products at the recommended addition rate, both the resultant Endure coatings achieve the following slip rating:

Tested to AS/NZS 4586-2004 Slip resistance classification of new pedestrian surface materials.

Appendix A : WET Pendulum = Class X

Appendix D : OIL - WET Ramp = Slip Resistance Assessment Group R12

To achieve the slip ratings indicated, the following system(s) must be used.

- One coat of Enviropro Timberseal.
- Two coats of Endure 1 Pack Satin or 2 Pack Satin. UltraGrip must be added to each coat of Endure.

UltraGrip is added to Endure at a rate of 5%. That is, 250g of UltraGrip into 5L of Endure (both 1 Pack and 2 Pack).

Specification Sheets for both Endure 1 Pack with UltraGrip and Endure 2 Pack with UltraGrip are available upon request. These Specification Sheets detail the coating system required, and mixing and application methods. Refer to the relevant Specification Sheet before starting.

Slip Test Certificates for both Endure 1 Pack with UltraGrip and Endure 2 Pack with UltraGrip are also available upon request.

Issue Date	18 th March 2009
Issued By	Keith Chu